

WILLIAM F. KEMPF & SON INC

900 ASHLAND AVENUE, FOLCROFT, PA 19032, USA

PHONE 610-532-2000 FAX: 610-534-3777

www.williamkempf.com

TREAD TILE SPECIFICATIONS

Style Number: 9001

Product Description: Heavy Duty Entrance Flooring tiles

Pile Material: Recycled rubber tyre and belt material

Tile Size: 305 mm x 305 mm

Total Weight: 9.88 kg/m² Total Thickness: 9.5 mm

Tiles per box: 25 (305 x 305 mm)

Backing: Non flammable solid adhesive base

Flammability: Meets federal regulation # DOCCFI 70

Exceeds minimum char radius, Average char per 8 strips tested $\frac{3}{4}$ " radius.

Coefficient of friction: ASTM F1677 Dry>1.0, Wet> 0.98

Radiant Panel: NFP 92-506 M3

Abrasion resistance: ASTM C501 Wear Index, 1/g = 53.9

Tensile Strength: ASTM D412 longitudinal>1500psi

Chemical Resistance:

Acetic Acid 30%	Fair
Butyl Alcohol	Good
Chromic Acid (dilute)	Good
Detergents	Good
Petroleum Products	Not resistant
Hydrogen Peroxide	Good
Nitric Acid	Not resistant
Sodium Hydroxide	Good
Sulphuric Acid (dilute)	Good